Telefax: +49 7941-646 88 55



Safety Data Sheet

according to UK REACH Regulation

ILKA-Rapid

Revision date: 24.11.2022 Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ILKA-Rapid

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Farbentferner / Klebstoffentferner / Abbeizer

For commercial users/professionals only!

1.3. Details of the supplier of the safety data sheet

Company name: ILKA-Chemie GmbH Street: Danziger Str. 21 Place: D-74613 Öhringen +49 7941-646 88 0

e-mail: post@ilka-chemie.com Internet: www.ilka-chemie.com

1.4. Emergency telephone Giftnotruf München: +49 89-19 240

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 3; H226 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

n-butyl acetate

Signal word: Warning

Pictograms:





Hazard statements

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P312 Call a POISON CENTER/doctor if you feel unwell.

P370+P378 In case of fire: Use Foam to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container to waste collection.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.



ILKA-Chemie GmbH

according to UK REACH Regulation

ILKA-Rapid

Revision date: 24.11.2022 Page 2 of 10

2.3. Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or does not fall under Annex XIII of Regulation (EC) 1907/2006 (< 0.1%)

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of the substances listed below with harmless additions

Hazardous components

CAS No	Chemical name			Quantity
	EC No Index No REACH No			
	Classification (GB CLP Regulation)			
123-86-4	n-butyl acetate			50 - < 100 %
	204-658-1 607-025-00-1 01-2119485493-29			
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			

Full text of H and EUH statements; see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name			
	Specific Conc. Limits, M-factors and ATE				
123-86-4	204-658-1	n-butyl acetate	50 - < 100 %		
	inhalation: LC50 = 23,4 mg/l (vapours); dermal: LD50 = >14112 mg/kg; oral: LD50 = 10760 mg/kg				

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink 1 glass of of water. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation of high vapor concentrations can cause symptoms such as headache, dizziness, fatigue, nausea and vomiting. Degreases the skin and makes it dry and rough. Prolonged or repeated skin contact may cause dermatitis. See item 11 for more information on symptoms and health hazards.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media



ILKA-Chemie GmbH

according to UK REACH Regulation

ILKA-Rapid

Revision date: 24.11.2022 Page 3 of 10

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

Full water iet

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air. Vapours are heavier than air, spread along floors and form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For non-emergency personnel

No action should be taken that involves personal risk are associated or have not been adequately trained. evacuate the area. Not Deny necessary and unprotected personnel access. buried Do not touch or step on substance. Inhalation of vapor or mist avoid. Ensure adequate ventilation. With insufficient ventilation wear respirator. Put on suitable personal protective equipment

For emergency responders

Do not attempt to operate without proper protective equipment. More information: see Section 8 "Exposure controls/Personal Protective gear".

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.



according to UK REACH Regulation

ILKA-Rapid

Revision date: 24.11.2022 Page 4 of 10

For commercial users/professionals only!

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately.

Wash hands and face before breaks and after work and take a shower if necessary.

Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme.

When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Farbentferner / Klebstoffentferner / Abbeizer

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
123-86-4	n-butyl acetate			
Consumer DN	NEL, long-term	oral	systemic	2 mg/kg bw/day
Consumer DN	NEL, acute	oral	systemic	2 mg/kg bw/day
Consumer DN	NEL, long-term	dermal	systemic	6 mg/kg bw/day
Consumer DN	NEL, acute	dermal	systemic	6 mg/kg bw/day
Consumer DN	NEL, acute	inhalation	systemic	859,70 mg/m³
Consumer DN	NEL, acute	inhalation	local	300 mg/m³
Consumer DN	NEL, long-term	inhalation	systemic	35,7 mg/m³
Consumer DN	NEL, long-term	inhalation	local	35,7 mg/m³
Worker DNEL	., long-term	dermal	systemic	11 mg/kg bw/day
Worker DNEL	., acute	dermal	systemic	11 mg/kg bw/day
Worker DNEL	., acute	inhalation	systemic	960 mg/m³
Worker DNEL	., acute	inhalation	local	600 mg/m³
Worker DNEL	., long-term	inhalation	systemic	300 mg/m³
Worker DNEL	_, long-term	inhalation	local	300 mg/m³



according to UK REACH Regulation

ILKA-Rapid

Revision date: 24.11.2022 Page 5 of 10

PNEC values

CAS No	Substance		
Environment	al compartment	Value	
123-86-4	123-86-4 n-butyl acetate		
Freshwater		0,18 mg/l	
Marine water	r	0,018 mg/l	
Freshwater s	sediment	0,981 mg/l	
Marine sedin	nent	0,0981 mg/l	
Soil		0,0903 mg/kg	

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. Tightly sealed goggles (EN166)

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Multi-layer glove - PE / EVAL / PE> = 8 h

Skin protection

Use of protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: clear

Odour: characteristic

Melting point/freezing point:

Boiling point or initial boiling point and

126 °C

boiling range: Flammability

Solid/liquid: not applicable Gas: not applicable Lower explosion limits: 1,2 vol. % Upper explosion limits: 15 vol. % Flash point: 27 °C Auto-ignition temperature: 420 °C Decomposition temperature: not determined



according to UK REACH Regulation

ILKA-Rapid

Revision date: 24.11.2022 Page 6 of 10

pH-Value (at 20 °C): 6,2

Water solubility: easily soluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: 15 hPa

(at 20 °C)

Vapour pressure: 63 hPa

(at 50 °C)

Density (at 20 °C): 0,88 g/cm³
Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Oxidizing properties

The product is not: oxidising.

Other safety characteristics

Evaporation rate: not determined Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and used as directed

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name	Chemical name					
	Exposure route	Dose		Species	Source	Method	
123-86-4	n-butyl acetate						
	oral	LD50 mg/kg	10760	Rat	OECD 423		
	dermal	LD50 mg/kg	>14112	Rabbit	OECD 402		
	inhalation (4 h) vapour	LC50	23,4 mg/l	Rat			



according to UK REACH Regulation

ILKA-Rapid

Revision date: 24.11.2022 Page 7 of 10

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (n-butyl acetate)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

The product is not: Ecotoxic.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
123-86-4	n-butyl acetate						
	Acute fish toxicity	LC50	18 mg/l		Pimephales promelas (fathead minnow)		
	Acute algae toxicity	ErC50 mg/l	647,7		Desmodesmus subspicatus	Wachstumsrate	
	Acute crustacea toxicity	EC50	44 mg/l		Daphnia magna (Big water flea)	Wachstumsrate	
	Crustacea toxicity	NOEC	23 mg/l		Daphnia magna (Big water flea)		

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
123-86-4	n-butyl acetate			
	OECD 301 D	83 %	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
123-86-4	n-butyl acetate	2,3

BCF

CAS No	Chemical name	BCF	Species	Source
123-86-4	n-butyl acetate	23,2		



according to UK REACH Regulation

ILKA-Rapid

Revision date: 24.11.2022 Page 8 of 10

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1123

14.2. UN proper shipping name: BUTYL ACETATES

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Marine transport (IMDG)

14.1. UN number or ID number: UN 1123

14.2. UN proper shipping name: BUTYL ACETATES

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Special Provisions: 223
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-D

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No





according to UK REACH Regulation

ILKA-Rapid

Revision date: 24.11.2022 Page 9 of 10

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

2010/75/EU (VOC): 100 % (880 g/l) 2004/42/EC (VOC): 100 % (880 g/l)

Information according to 2012/18/EU P5c FLAMMABLE LIQUIDS

(SEVESO III):

Additional information

Regulation (EC) No. 648/2004 [Detergents regulation].

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative





according to UK REACH Regulation

ILKA-Rapid

Revision date: 24.11.2022 Page 10 of 10

RID: Regulations concerning the international carriage of dangerous goods by rail

EmS: Emergency Schedules MFAG: Medical First Aid Guide

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety

assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)