



ILKA - Siloxan

Special impregnation against damages caused by the atmosphere

Characteristics:

1. Protection against penetration of moisture, water spots, efflorescence, fungal- and moss attack, damages done by frost or extreme heat.
2. Protection against soiling on every sort of plaster, on concrete, mortar, splits, earthen wares, natural- and artificial stones, asbestos and transits, dead plaster, insulating materials.

The treated surfaces will be weather- and freeze-proof. There will be no discolouration. We give five year's guarantee of the product under condition of an appropriate usage.

Attention: Inflammable. Keep it inside a cool place.

Operative Range:

Usable for all surfaces treated with our products ILKA-SZ, ILKA-Stone Cleaner S, ILKA-Stone Cleaner FSV, ILKA-Stone Cleaner A, ILKA-Stone Cleaner AP, ILKA Salpetertod, for all absorbent stones.

Application:

Distribute it fully on an air-dried surface using a paint brush, a brush or an atomizer. To be sure that the surface is completely protected, the using of the flooding procedure is recommended. Application only at temperatures over + 10 degrees. Protect the cleaned surfaces for one day against rain. Consumption: 1 litre on 2-6 m² due to surface absorbency.

Protective Measures:

Wear protection clothes. In case the eyes or the skin come into contact with the product, rinse them vigorously with clear water.

Packing devices: 10, 20, 30, 100, 200 litres.

Our directions as to technical use, are based on thorough tests in the laboratory and know-how. Considering the various practicable conditions, the given information and recommendation is, however, without any obligation.

ILKA-CHEMIE GmbH GERMANY

Alte Str. 11 • D-74629 Pfedelbach • Tel: +49 7141 / 9906-51 oder -53 • Fax: +49 7141 / 9906-54
[http:// www.ilka-chemie.com](http://www.ilka-chemie.com) • E-mail: post@ILKA-Chemie.com